


# Calibration Pocket Guide

For guidance only. Always check your spreader settings. Download the free AXCELA™ calibration app from [www.axcela.eu](http://www.axcela.eu) or check the website for advice on manual calibration checks.



\* Recommended for spreading width up to 24 m

## AMAZONE - ZA-M 1200 DW – Application Rates\*

4 kg/ha					5 kg/ha					6 kg/ha					7 kg/ha									
12	8	0.64	3.1	23/54	12	8	0.8	3.5	23/54	12	8	0.96	3.9	23/54	12	8	1.12	4.3	23/54					
	10	0.8	3.5			10	1.0	4.0			10	1.2	4.4			10	1.4	4.9						
	12	0.96	3.9			12	1.2	4.4			12	1.44	5.0			12	1.68	5.5						
	14	1.12	4.3			14	1.4	4.9			14	1.68	5.5			14	1.96	6.1						
18	8	0.96	3.9	23/54	18	8	1.2	4.4	23/54	18	8	1.44	5.0	23/54	18	8	1.68	5.5	23/54					
	10	1.2	4.4			10	1.5	5.1			10	1.8	5.8			10	2.1	6.4						
	12	1.44	5.0			12	1.8	5.8			12	2.16	6.5			12	2.52	7.3						
	14	1.68	5.5			14	2.1	6.4			14	2.52	7.3			14	2.94	8.1						
24	8	1.28	4.6	25/56	24	8	1.6	5.3	25/56	24	8	1.92	6.0	25/56	24	8	2.24	6.7	25/56					
	10	1.6	5.3			10	2.0	6.2			10	2.4	7.0			10	2.8	7.8						
	12	1.92	6.0			12	2.4	7.0			12	2.88	8.0			12	3.36	8.9						
	14	2.24	6.7			14	2.8	7.8			14	3.36	8.9			14	3.92	9.9						

## APV CLASSIC M2 – Application Rates\*

4 kg/ha					5 kg/ha					6 kg/ha					7 kg/ha									
12	8	0.64	2.1	-	12	8	0.8	2.2	-	12	8	0.96	2.3	-	12	8	1.12	2.4	-					
	10	0.8	2.2			10	1.0	2.3			10	1.2	2.5			10	1.4	2.7						
	12	0.96	2.3			12	1.2	2.5			12	1.44	2.7			12	1.68	3.0						
	14	1.12	2.4			14	1.4	2.7			14	1.68	3.0			14	1.96	3.3						
18	8	0.96	2.3	-	18	8	1.2	2.5	-	18	8	1.44	2.7	-	18	8	1.68	3.0	-					
	10	1.2	2.5			10	1.5	2.8			10	1.8	3.1			10	2.1	3.5						
	12	1.44	2.7			12	1.8	3.1			12	2.16	3.6			12	2.52	4.1						
	14	1.68	3.0			14	2.1	3.5			14	2.52	4.1			14	2.94	4.9						
24	8	1.28	2.6	-	24	8	1.6	2.9	-	24	8	1.92	3.2	-	24	8	2.24	3.7	-					
	10	1.6	2.9			10	2.0	3.4			10	2.4	3.9			10	2.8	4.6						
	12	1.92	3.2			12	2.4	3.9			12	2.88	4.8			12	3.36	5.8						
	14	2.24	3.7			14	2.8	4.6			14	3.36	5.8			14	3.92	7.1						

## BOGBALLE-M2 – Application Rates \*

4 kg/ha					5 kg/ha					6 kg/ha					7 kg/ha									
12	8	0.64	0.8	E6 Vane on 1 and 2 Tilt : -2°	12	8	0.8	0.9	E6 Vane on 1 and 2 Tilt : -2°	12	8	0.96	0.9	E6 Vane on 1 and 2 Tilt : -2°	12	8	1.12	1.0	E6 Vane on 1 and 2 Tilt : -2°					
	10	0.8	0.9			10	1.0	1.0			10	1.2	1.1			10	1.4	1.2						
	12	0.96	0.9			12	1.2	1.1			12	1.44	1.2			12	1.68	1.4						
	14	1.12	1.0			14	1.4	1.2			14	1.68	1.4			14	1.96	1.5						
18	8	0.96	0.9	E6 Vane on 3 and 4 Tilt : 0°	18	8	1.2	1.1	E6 Vane on 3 and 4 Tilt : 0°	18	8	1.44	1.2	E6 Vane on 3 and 4 Tilt : 0°	18	8	1.68	1.4	E6 Vane on 3 and 4 Tilt : 0°					
	10	1.2	1.1			10	1.5	1.3			10	1.8	1.4			10	2.1	1.6						
	12	1.44	1.2			12	1.8	1.4			12	2.16	1.6			12	2.52	1.8						
	14	1.68	1.4			14	2.1	1.6			14	2.52	1.8			14	2.94	2.1						
24	8	1.28	1.1	E6 Vane on 3 and 4 Tilt : +2°	24	8	1.6	1.3	E6 Vane on 3 and 4 Tilt : +2°	24	8	1.92	1.5	E6 Vane on 3 and 4 Tilt : +2°	24	8	2.24	1.7	E6 Vane on 3 and 4 Tilt : +2°					
	10	1.6	1.3			10	2.0	1.5			10	2.4	1.8			10	2.8	2.0						
	12	1.92	1.5			12	2.4	1.8			12	2.88	2.1			12	3.36	2.3						
	14	2.24	1.7			14	2.8	2.0			14	3.36	2.3			14	3.92	2.7						

## DELIMBE DELIMBE T28 – Application Rates\*

4 kg/ha					5 kg/ha					6 kg/ha					7 kg/ha									
12	8	0.64	10.6	-	12	8	0.8	11.3	-	12	8	0.96	12.1	-	12	8	1.12	12.8	-					
	10	0.8	11.3			10	1.0	12.2			10	1.2	13.2			10	1.4	14.1						
	12	0.96	12.1			12	1.2	13.2			12	1.44	14.2			12	1.68	15.3						
	14	1.12	12.8			14	1.4	14.1			14	1.68	15.3			14	1.96	16.5						
18	8	0.96	12.1	-	18	8	1.2	13.2	-	18	8	1.44	14.2	-	18	8	1.68	15.3	-					
	10	1.2	13.2			10	1.5	14.5			10	1.8	15.8			10	2.1	17.1						
	12	1.44	14.2			12	1.8	15.8			12	2.16	17.4			12	2.52	18.8						
	14	1.68	15.3			14	2.1	17.1			14	2.52	18.8			14	2.94	20.5						
24	8	1.28	13.5	-	24	8	1.6	14.9	-	24	8	1.92	16.3	-	24	8	2.24	17.7	-					
	10	1.6	14.9			10	2.0	16.7			10	2.4	18.3			10	2.8	19.9						
	12	1.92	16.3			12	2.4	18.3			12	2.88	20.3			12	3.36	22.0						
	14	2.24	17.7			14	2.8	19.9			14	3.36	22.0			14	3.92	24.0						



**Distributed by:**  
Lonza Cologne GmbH  
Nattermannallee 1 D-50829 Köln, Germany  
Tel: ++49 (0) 221 99 1990  
Fax: ++49 (0) 221 99 19911

**Produced by:**  
Lonza AG, Walliser Werke,  
Rottenstrasse 6, CH-3930 Visp, Switzerland  
Tel: ++41-61-316-81-11  
Fax: ++41-61-316-91-11

AXCELA™ is a trademark of Lonza Ltd. META® is a registered trademark of Lonza Ltd.  
Bitrex® is a registered trademark of Macfarlan Smith Ltd.

Use plant protection products safely. AXCELA™ contains metaldehyde.  
Always read the label and product information before use. For details of warning phrases and symbols relating to AXCELA™, please use [www.axcela.eu](http://www.axcela.eu)

**LEHNER** LEHNER SUPER VARIO – Application Rates\*

4 kg/ha					5 kg/ha					6 kg/ha					7 kg/ha				
12	8	0.64	20.4	-															
	10	0.8	22.2	-															
	12	0.96	24.0	-															
	14	1.12	25.7	-															
18	8	0.96	24.0	-															
	10	1.2	26.6	-															
	12	1.44	29.2	-															
	14	1.68	31.7	-															
24	8	1.28	27.5	-															
	10	1.6	30.8	-															
	12	1.92	34.1	-															
	14	2.24	37.3	-															

**RAUCH** RAUCH AXIS 30.1W – Application Rates\*

4 kg/ha					5 kg/ha					6 kg/ha					7 kg/ha				
12	8	0.64	2.6	4.0															
	10	0.8	2.7	4.0															
	12	0.96	2.8	4.0															
	14	1.12	2.9	1.0															
18	8	0.96	2.8	6.5															
	10	1.2	2.9	5.5															
	12	1.44	3.1	1.0															
	14	1.68	3.3	1.0															
24	8	1.28	3.0	9.5															
	10	1.6	3.2	8.5															
	12	1.92	3.5	7.0															
	14	2.24	3.7	7.0															

**StocksAG** STOCKS FAN JET PRO – Application Rates\*

4 kg/ha					5 kg/ha					6 kg/ha					7 kg/ha				
12	8	0.64	2.2	-															
	10	0.8	2.4	-															
	12	0.96	2.5	-															
	14	1.12	2.7	-															
18	8	0.96	2.5	-															
	10	1.2	2.8	-															
	12	1.44	3.0	-															
	14	1.68	3.2	-															
24	8	1.28	2.8	-															
	10	1.6	3.1	-															
	12	1.92	3.4	-															
	14	2.24	3.7	-															

**SULKY** SULKY X44 – Application Rates\*

4 kg/ha					5 kg/ha					6 kg/ha					7 kg/ha				
12	8	0.64	4.1	127/123															
	10	0.8	4.5	127/123															
	12	0.96	4.9	127/123															
	14	1.12	5.2	127/123															
18	8	0.96	4.9	127/123															
	10	1.2	5.4	127/123															
	12	1.44	6.0	127/123															
	14	1.68	6.5	127/123															
24	8	1.28	5.6	130/127															
	10	1.6	6.3	130/127															
	12	1.92	6.9	130/127															
	14	2.24	7.5	130/127															

**Vicon** VICON RS XL – Application Rates\*

4 kg/ha					5 kg/ha					6 kg/ha					7 kg/ha				
12	8	0.64	7.6	-															
	10	0.8	8.4	-															
	12	0.96	9.1	-															
	14	1.12	9.8	-															
18	8	0.96	9.1	-															
	10	1.2	10.1	-															
	12	1.44	11.0	-															
	14	1.68	11.9	-															
24	8	1.28	10.4	-															
	10	1.6	11.6	-															
	12	1.92	12.7	-															
	14	2.24	13.7	-															

Spread (m)  
 Speed (km/h)  
 Feed (kg/min)  
 Index  
 Disc (OM)

**axCela**™  
Kills more slugs, more quickly